VACRON
ADVANCES IN SECURITY SOLUTIONS

NEW

ONVIF

5 Megapixel IR Bullet IP Camera



NEW 2014 SEP. V1.0





IP Surveillance

VIG-UM731VE

- 5 Mega Pixel 1/3.2" CMOS Image Sensor.
- Real-time H.264, MJPEG Compression(Dual Codec).
- Resolution : 2560x1920.
- Simultaneous Multiple Streams.
- 42 IR LEDs, IR range 30M
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability.

VIG-UM731VE 5 Megapixel IR Bullet IP Camera


5 MEGA PIXEL | 1/3.2" CMOS | LENS 2.8-12 mm | 42 LEDs | 30 M | IRCut | H.264 | 30 FPS | IP 66 | P.O.E


Full function cable (Optional)



1. GND
2. Alarm output 1
3. Alarm input 2
4. Alarm input 1
5. DC12V input
6. Reset Button
7. Analog Video Out
8. Audio Line in
9. RJ-45 Ethernet LAN Port

Dimension Unit: mm






SPECIFICATIONS

System	Flash：16MB	
	RAM：256MB	
Image Sensor	5 Megapixel High Quality 1/3.2 CMOS Image Sensor	
Sensitivity	0 Lux (IR ON)	
IR LEDs	42PCS	
IR Range	30M	
Lens	Varifocal 2.8~12mm F1.4	
	Removable IR-cut filter for day & night function	
Video	H.264: 5MP(2560 x 1920) @10fps	
	H.264: 3MP(2048 x 1536) @25fps	
	H.264: 1600 x 1200 @30fps	
	H.264: 1080P @30fps	
	H.264: 720P @30fps	
	H.264: VGA @30fps	
	H.264: 270P @30fps	
	H.264: 352 x 240 @30fps	
	Compression: H.264, MJPEG Streaming: Dual Codec (H.264、JPEG) Selectable	
	Support Simultaneous multiple streams	
	BNC connector for video output, NTSC/PAL video output switch	
Image Settings	Adjustable image size, quality, and bit rate	
	Time/Date stamp and text caption overlay.	
	BNC connector for video output, NTSC/PAL video output switch	
	Adjustable image size, quality, and bit rate	
	Time/Date stamp and text caption overlay.	
	Configurable brightness, contrast, saturation, sharpness, white balance and exposure	
	AGC / AWB / AES / BLC / WDR	
Audio	Format	G.711 audio encoding
	Support Audio line-in for external microphone(Optional)	
Networking	Interface	10/100 Mbps Ethernet, RJ-45
	Supported Protocol	IPv4,TCP/IP,DHCP,HTTP,RTSP,SNTP,DNS
	Supported Browser	Microsoft Internet Explorer 6.0 or above
Alarm and Event	Motion Detection	
Managemnent	Event notification using SMTP or FTP	
Users	8 clients on-line monitoring at the same time	
	Multi-level user access control with password protection	
Maintenance	Supports online firmware upgrade	
I/O port	RJ-45 Ethernet x 1, DC Jack x 1	
	BNC Video out, Phone Jack Line in x 1, Alarm I/O, Reset Botton(Optional)	
On-board Storage	SD/SDHC card slot : Stores snapshots and video clips(Optional)	
IP Rating	IP66	
Power	DC12V or PoE IEEE802.3af Class 0	
Max. Power Consumption	3.6W(IR OFF),7W(IR ON)	
Weight	Netweight: 965g	
Dimension	315 × 88 × 87 mm	
Operating Environments	Temperature: 0 ~ 45 °C	Humidity: 90%

★Product specifications are subject to change without notice; please contact us for the latest information.



■ DISTRIBUTED BY

VACRON ADVANCES IN SECURITY SOLUTIONS
FUHO TECHNOLOGY CO., LTD.
Head Office: No. 30, Lane 726, Jinma Rd, Sec. 3, Chang Hua City,Taiwan 500. TEL:886-4-751-2881 FAX:886-4-751-5860
www.vacron.com