



16 CH 1080P H.264

Network Video Recorder



IP Surveillance

VDH-NK350A

NEW 2014 SEP. V1.0




- Auto detect IP camera in LAN.
- Multiplex and maximize hard drive performance
- Sequence feature for easy liveview monitoring.
- Motion events mark on time bar for faster event searching during playback.
- P2P functionality.
- QR Code scanning for fast auto connection.
- Cloud real-time monitoring.
- Support SATA / SATA II hard drive up to 8TB.

VDH-NK350A

16CH H.264 Network Video Recorder

■ INSTALLATION



1. POWER
2. USB 2.0
3. USB 3.0
4. HD OUT
5. AUDIO OUT
6. LAN
7. VGA OUT
8. E-SATA(optional)

■ SPECIFICATIONS

System	Operating system : Linux
Storage	Build in SATA interface x 2, compatible SATA/SATAII/SATA III HDD(Max. 8TB)
Device/Interface	E-SATA *1 (Max 16T) Optional
Video And Other	Dual video : HD OUT/VGA
I/O Interface	USB 2.0 *2
	USB 3.0 *1
	Headphones (speakers) sound output x1
	Ethernet x1 – 10/100/1000 (IEEE 802.3 Type 10Base-T / IEEE 802.3u Type 100Base-TX / I) : Auto-MDIX
Network Protocol	Ipv4 / ARP / TCP / UDP / ICMP / SMTP / HTTP / RTP / RTSP / RTCP
Video Format	H.264 compression format
Live / Playback	E-Map
	Real-time Live View capable 16CH VGA @30fps
	4CH 1080P @23fps Synchronous Playback
	Recording Query: Time search, Event search (IP CAM displacement, alarm notification)
	Playback speed/ slow forward / fast forward in 5 different speed, Play Frame by Frame mode (forward or backward)
Event Notification	Pentaplex operation: Live/ Record/ Playback
	Event Notification : Motion detection, Video loss, HDD error
	Recording Mode
	Constant recording
	Schedule recording
Backup Management	Alarm triggered recording (include motion detection recording): Complete event video reserved 3 seconds before and 60 minutes after event taken place.
	Schedule alarm triggered recording (include motion detection recording): Complete event video reserved 3 seconds before and 60 minutes after event taken place.
	Manual recording
	Only recording without live (depending on user authority)
	Video output format: AVI
System Management	The USB mobile storage device or remote NAS
	Remote Client software; live, playback set up by PC (remote side)
	Authorization: Maximum 10 group accounts, Hierarchical authority
	Support 3 users log on by Client-side software or browser.
	Systems operation records, record login time, IP and selected video.
Support Equipment	Browser: MS IE7-IE9
	Support megapixel IP Camera video
	Support CCTV camera video via Video Server.
Power	DC12V / 4.16A
Operating Temperature	0-45°C
Weight	About 1.7kg
Dimension	168mm x 172mm x 19.5mm (W x D x H)

*Product specifications are subject to change without notice; please contact us for the latest information.

■ DISTRIBUTED BY

